



DAM.HİD.MAK.SAN.TİC.LTD.ŞTİ.
SEMITÜRK

MODEL:

STUP031660 3x16 Meter 60 Ton Truck Unloading Platform



SEMITÜRK



BÜYÜKYÜKSEL DAMPER VE HİDROLİK MAK. SAN. TİC. LTD. ŞTİ.


TRADEMARK NAME: SEMITURK

FEVZİ ÇAKMAK MAH. MEDCEZİR CAD. NO: 8/116 B BLOK KONYA / TÜRKİYE

www.yukseldamper.com.tr - www.semiturk.com.tr

E-mail: info@yukseldamper.com.tr - Tel: +90 332 239 1860 / +90 530 610 1432

BÜYÜKYÜKSEL
DAM.HİD.MAK.SAN.TİC.LTD.ŞTİ.
SEMITÜRK


Truck Unloading Platform
STUP031660

Weights & Dimensions (± 5%)	Product	Hydraulic Truck Unloading Platform Truck Dumpers Truck Tipper Platform
	Installation Type	Channel Type (<u>optional</u> above-ground, side-tilting or other types and/or special design)
	Size of Platform (WxL)	3 Meter (W) x 16 Meter (L) (<u>optional</u> 3x18, 3x20 or other sizes and/or special design)
	Lifting Capacity	60 Tons gross weight (<u>optional</u> 80 Tons, 100 Tons or other capacity and/or special design)
	Tilting / Opening Angle	38° (varies depending on <u>optional</u> options)
	Tare Weight	12.000 kg ± 10% with accessories (varies depending on <u>optional</u> options)
Body / Chassis	Main chassis are produced from "IPE 450" profile. Other body/structure metal parts produced from box profile and 'ST37/S235' quality sheet (<u>or optional</u> other material options according to needs and also varies depending on <u>optional</u> options)	
Sub-frame	Produced from '200x200x5mm profile' <u>or</u> 'NPU 200' profile and reinforced with supports	
Floor Sheet	Floor sheet 7/8 mm non-skid chequered <u>or</u> 8 mm ST37/S235 sheet (<u>or optional</u> other options)	
Wheel Holders / Stoppers	2 rows of hydraulically controlled wheel holders that working as pair (right - left)	
Balance Plate	A balance plate is placed under the platform to absorb unbalanced loads as mechanically	
Hydraulic Cylinder/s (For Rear Tipping)	2 pcs 215-5-7000 <u>or</u> 1 pcs 245-5-7000 hydraulic cylinder/s <u>optional</u> other combinations	
Hydraulic Unit	Placed under the platform, includes hydraulic and electrical equipment and accessories	
Hydraulic Valve/s	24V DC continuous operation type <u>optional</u> other combinations	
Hydraulic Pump (Varies depending on options)	1 pcs 65-97 l/m gear <u>or</u> piston pump and 1 pcs 9cc gear pump <u>optional</u> other combinations	
Electrical Motors (Varies depending on options)	1 pcs 3x380 Volt - 1500 rpm 30-37 kW and 1 pcs 2-4 kW electrical motor that flanged type	
Equipment Control (Remote & Manual Control)	PLC controlled remote control system and manually control buttons from panel (up-down)	
Paint (with up to date RAL colour options)	Metal parts are painted 1-layers anti-corrosive epoxy primer then top acrylic paint coat	
Standard Accessories	Oil cooler radiator or oil heater, limit switch sensor, hydraulic filter, oil tank, oil temperature gauge, oil level gauge, oil pressure gauge, oil inlet cap and ventilation cap, R2 type high pressure hoses and other required accessories	
Optional Features / Hardwares	Lubrication, overflow, high and low voltage warning display hardware and software system	

BÜYÜKYÜKSEL DAMPER VE HİDROLİK MAK. SAN. TİC. LTD. ŞTİ.
TRADEMARK NAME: SEMITURK
FEVZİ ÇAKMAK MAH. MEDCEZİR CAD. NO: 8/116 B BLOK KONYA / TÜRKİYE
www.yukseldamper.com.tr - www.semiturk.com.tr
E-mail: info@yukseldamper.com.tr - Tel: +90 332 239 1860 / +90 530 610 1432