

### Body / Chassis :

Manufactured from high-strength steel by using special submerged welding machines. Chassis, frame and backbone structure are suitable for heavy-loads and difficult site conditions and designed for an esthetic appearance and durability. Used materials

- Floor sheet; "7/8 mm checkered sheet"
- Reinforced goose-neck
- Main chassis "Domex700"

### Axles :

- 6 axles, 12 ton capacity
- Square section
- 3 self-steering axles

### Front Axles Lifting :

2 Front axle lifting operated from the cab, protracting the tire life-cycle.

### King-Pin :

2" bolt-connected in DIN Standards; interchangeable with 3.5"

### Landing Legs :

Telescopic landing legs mechanical with two speeds,

Dynamic: 25 000 kg, Static: 50 000 kg

### Rear Loading Ramps:

- 24 volt electrical mini power-pack
- Hydraulic flow divider
- Vehicle connection socket in front of Lowbed
- Rear loading ramps, 4 way hydraulic motion

### Brake System :

- Dual circuit brake hardware
- 30" Service brake bellows
- 30x30" Emergency brake bellows
- Load balancing distribution valve
- Automatic brake adjusters
- EBS Brake System "WABCO"

### Suspension System :

- Air -suspension "5813"
- 100 mm Z-type springs
- "WABCO" suspension valves
- Shock Absorbers

### Electricity Hardware : "E Certified"

- 24 Volt Lighting System
- 7 pole distribution cable
- Electrical socket for lighting
- 4 x 2 side lamps
- Required hardware for traffic

<< All measures are declared with 2% margin >>

### Dimensions:

- Total length : 14,500 mm
- Telescopic chassis :
- Total overall width : 2.850 mm
- Loading platform length : 10,400 mm
- Platform height : 980 mm
- Side extension profiles : 250+250 mm
- Gross vehicle weight : 74,000 kg

### Tires : Good year - Pirelli - Bridgestone

- 235 / 75 R 17.5" size, 24 + 1 units tubeless tires and steel rims

**Painting :** All Steel plates and structure are blasted, painted with two anti-corrosive primer coats and two levels topcoat with your colors.

### Standard Accessories :

- 1 x Spare tire holder
- 1 x Water tank "Chrome Nickel"
- Parking chock with handle

### Optional:

Foldable rear loading ramp  
4x6 mt telescopic chassis

REMARK : Our products are under 2 years local and one year international warranty against manufacturing defects.

As total semi-trailer weight was designed for 13,992.kg, Domex Swedish steel is used in critical spots to not reduce the strength

