

Body / Chassis :

Manufactured from high-strength steel by using special submerged welding machines. Chassis, frame and backbone structure are suitable for heavy-loads and difficult site conditions and designed for an esthetic appearance and durability. Used materials;

Axles :

- 3 axles, 12 ton capacity, square section

Front Axle Lifting :

Operated from the cab, protracting the tire life-cycle.

Landing Legs :

“S 2000 plus” model telescopic landing legs mechanical with two speeds,
Dynamic: 25 000 kg,Static: 50 000 kg

King-Pin :

2” bolt-connected in DIN Standards, interchangeable with 3.5”.

Brake System :

- Dual circuit brake hardware,
- 30” Service brake bellows
- 30x30” Emergency brake bellows
- Load balancing distribution valve,
- Automatic brake adjusters,
- EBS Brake System “WABCO”

Suspension System :

- Air -suspension “5813”,
- 100 mm Z-type springs,
- “WABCO” suspension valves,
- Shock Absorbers

Electricity Hardware :

- 24 Volt Lighting System
- 7 pole distribution cable
- Electrical socket for lighting,
- Required hardware for traffic

<< All the dimensions are with 2% margin >>

Dimensions :

- Total length :
- Total overall width :

Tires : Good year - Pirelli - Bridgestone
385 / 65 R 22.5” size, 6+1 units tubeless tires and steel rims

Painting : All steel parts are blasted, painted with two layers of anti-corrosive primer coats and top acrylic paint coat with up-to-date colours and design.

Standard Accessories :

- 1 x Spare tire holder
- FRP Mudguards
- Ladder
- 1 x Tool box “imported, plastic”
- 1 x Water tank “Chrome Nickel”
- Parking chock with handle.

REMARK : Our products are under 2 years local and one year international warranty against manufacturing defects.

