

Body / Chassis:

Manufactured from high-strength steel by welding machines. Chassis, frame and backbone structure are suitable for heavy-loads and difficult site conditions and designed for esthetic appearance and durability.

- Bottom hydraulic system
- Reinforced moving Hardox floor editions
- Reinforced 2.5 mm Hardox side walls with 3 mm Domex vertical bars,
- Pneumatic, very light and durable back door design,
- Fiber front panel,
- All functions are controlled by remote control
- Reinforced, stable, light and esthetic chassis,

Axles:

- 3 axles, each one 12 ton capacity
- Front axle is lift able

Landing Legs:

Telescopic landing legs mechanical with two speeds. Static: 50 Tons, Dynamic: 25 Tons

King-Pin:

2" bolt-connected in DIN Standards (D:152 kN - Type: H50-X); interchangeable with 3½"

Brake System:

- Standard dual circuit brake hardware
- 30" Service brake bellows
- 30x30" Emergency brake bellows
- Automatic brake slack adjusters
- Standard 2S/2M EBS Brake System "WABCO/KNORR"

Suspension System:

- Air suspension system (Standard Equipment) in European standard
- 813 type suspension bellows
- 100 mm Z-type springs
- Shock absorbers
- Other standard equipments

Electrical Hardware (ADR Norms):

- 24 V, optional 12V Lighting System
- Standard ASPOCK or SA-BA Brands
- Standard 7, optional 15 pins distribution cable
- Side, front and rear lamps,
- Other needed equipment for your countries traffic regulations

<< All measures are declared with 2% margin >>

Dimensions:

- Total Length : 10.305 mm
- Total overall width : 2.553 mm
- Inside cover height : 1.000 mm
- Weight : 7.450 Kg

Tires: Lassa - Pirelli - Bridgestone - Good Year 385/65/ R 22.5 size, 6 units tubeless tires and steel rims.

Painting: All steel parts are blasted, painted with two layers of anti-corrosive primer coats and top acrylic paint coat with up-to-date colors.

Standard Accessories:

- 6 x FRP fenders
- 1 x Tool box
- 1 x Water tank "Chrome Nickel"
- Parking chock with handle
- Lateral protection device

Optional:

- Polyester and automatic controlled up tarpaulin system
- Aluminum rims

REMARK: Our products are under 1 years warranty against manufacturing defects.



